

# WavePOS 9690



Ready in Windows / Android Systems



Flat Touch Screen



LCM Customer Display



MSR / RFID

MODEL	WavePOS 9690			
CPU	Intel® Celeron® Elkhart Lake J6412 Processor	Intel® Tiger Lake Core™ i3-1115G4 Processor	Intel® Tiger Lake Core™ i5-1135G7 Processor	Quad-core Cortex-A55 RK3568 Processor
Memory	1 x 4GB DDR4 SO-DIMM slot up to 16GB	2 x 4GB DDR4 SO-DIMM slot up to 64GB	2 x 4GB DDR4 SO-DIMM slot up to 64GB	4GB LPDDR4
Storage	1 x M.2 2242	1 x M.2 2242 1 x M.2 2280 (Option)	1 x M.2 2242 1 x M.2 2280 (Option)	64GB eMMC 1 x Micro SD slot
Power	60W~120W (24V)	90W~120W (24V)	90W~120W (24V)	60W (24V)
Display	15.6" TFT-LCD			
Resolution	1366 x 768 or 1920x1080 (Option)			
Touch Screen	PCAP Multitouch Screen / 10 Points			
Brightness	400 nits			
Weight	3.8 kgs	4.0 kgs	4.0 kgs	3.8 kgs
Dimensions	340 x 300 x 214mm (W x H x D)			
Audio	2 x 2W Speaker			
OS	Windows 10 IoT	Windows 10 IoT	Windows 10 IoT	Android 11
Certifications	CE, FCC			
Environment	0°C ~ 40°C, 20% ~ 80% RH (Operating) -20°C ~ 60°C, 10% ~ 90% RH (Storage)			
I/O	3 x COM (RJ45), 1 x 12V/24V C/D (RJ11), 3 x USB 3.0, 1 x USB 2.0, 1 x Giga LAN (RJ45), 1 x Video Port, 1 x 24V DC-IN	3 x COM (RJ45), 1 x 12V/24V C/D (RJ11), 4 x USB 3.0, 1 x Giga LAN (RJ45), 1 x Video Port, 1 x 24V DC-IN	3 x COM (RJ45), 1 x 12V/24V C/D (RJ11), 4 x USB 3.0, 1 x Giga LAN (RJ45), 1 x Video Port, 1 x 24V DC-IN	1 x COM (RJ50), 1 x 12V/24V C/D (RJ11), 1 x USB 3.0, 3 x USB 2.0, 2 x Giga LAN (RJ45), 1 x Micro SD, 1 x Video Port, 1 x 24V DC-IN
<b>Option</b>				
I/O	Option A : 2 x USB 2.0 + 1 x Power USB 12V / Option B : 2 x USB 2.0 + 1 x Power USB 24V			
Peripheral	MSR, RFID, LCM, Printer, 2nd Display			